

ARMADA AREA SCHOOLS REQUEST FOR BID

PROJECT OVERVIEW:

Armada Schools is seeking quotes for new Combi Ovens at Armada Middle School, Armada High School and Krause Elementary School. Scope will include the ovens and water treatment systems. Installation to take place at a TBD date as equipment lead times allow. Delivery and Installation to be provided by Hobart Service.

Please e-mail your bid, no later than **October 18, 2023** to:

Armada Area Schools
Attn: Missy Elliott
Supervisor of Food Services
Melliott@armadaschools.org
P:586-784-2166

SPECIFICATIONS:

ARMADA MIDDLE SCHOOL

ITEM 1-COMBI OVEN, GAS (1 REQ'D)

Vulcan Model TCM-102G-NAT/LP Dimensions: 42.08(h) x 36.22(w) x 33.3(d)
Touch Combi Multi (TCM), 10 level full size, gas, boilerless, (10) 18"x 26"x 1" full sheet pan or (20) 12"x 20"x 2.5" steam pan capacity, (5) Grab n Go wire racks, twin control touch & knob, LCD display, Exclusive ABC, with JET & AUTO controls interface, customizable recipes & factory pre-programed, automatic cleaning with recirculation, auto descale, non proprietary chemicals, auto-reversing fan, LED light strip, cool touch door, USB port, multi point food probe, drain water tempering, 156,000 BTU, 120v/60/1-ph cord with plug, cULus, NSF, (VPJ102G-81)

NOTE: Item qualifies for a no charge equipment check out after the unit has been fully installed & put into service. contact your Vulcan Representative for more details
1 year limited parts & labor warranty, standard
K-12 School Nutrition extended warranty extends the warranty for 12 months beyond the 12 month Original Equipment Warranty, not to exceed 24 months from date of installation
Filtration System

NOTE: Water is a customer supplied utility just like Gas & Electric to the equipment. Proper Water Filtration based on customer water quality is essential to meet the equipment water spec requirements. Verify type of filtration needed based on performing a cold water analysis from the customer site. A suitable Water Treatment System & regular filter replacements coupled with routine cleaning/deliming is required.
V3MRO-2 Reverse Osmosis Water Filtration System, up to 200 gpd capacity (double combi units), minimum 60 psi/maximum 125psi, minimum 40°/maximum 100°, Common treatment for sediment, chloramines, chlorine, chloride, hardness & TDS reduction, integrated pump & storage tank, includes: wall-mount bracket, quick disconnect plumbing & special installation fittings kit for Vulcan Combi Oven/Steamers with standard 3/4" water lines & spray hose
TCM-RACK102 (5) Grab-and-Go Racks for, 18" x 26" pans on TCM units, standard
TCM-PROBE3 Multi-Point Food Probe, standard
VDL-1 Vulcan Detergent Liquid, 2.5 gal each, (2) per case (sold per case)

VRL-1 Vulcan Rinse Liquid, 2.5 gal each, (2) per case (sold per case)
(2) HOSEWTR 3/4BBV Flex stainless steel water hose 72", 3/4" female NSHT (2 per unit required for gas & electric, 3 with filter system, 1 per unit for direct steam)
TCM-STAND2 Deluxe Stand, with pan supports for 102 TCM units

INSTALLATION Delivery and Installation of new Combi Oven and Water Treatment System. Make Final Connections and check operation of equipment. To be Provided by:

Hobart Service
43442 N Interstate 94 Service Dr.
Belleville, MI 48111
P:734-697-3070

ITEM 2 -GAS CONNECTOR HOSE KIT / ASSEMBLY (1 kt REQ'D)

T&S Brass Model HG-2D-48SK

Safe-T-Link Gas Connector Kit, 3/4" connection, 48" hose, stainless steel braiding with extruded coating, (2) Swivelink fittings, (1) 90° elbow, ball valve, necessary hardware, with Surelink restraining cable adjustable for 3' to 5', 215,000 BTU/ hr minimum flow capacity

ARMADA HIGH SCHOOL

ITEM 1-COMBI OVEN, GAS (1 REQ'D)

Vulcan Model TCM-102G-NAT/LP Dimensions: 42.08(h) x 36.22(w) x 33.3(d)

Touch Combi Multi (TCM), 10 level full size, gas, boilerless, (10) 18"x 26"x 1" full sheet pan or (20) 12"x 20"x 2.5" steam pan capacity, (5) Grab n Go wire racks, twin control touch & knob, LCD display, Exclusive ABC, with JET & AUTO controls interface, customizable recipes & factory pre-programed, automatic cleaning with recirculation, auto descale, non proprietary chemicals, auto-reversing fan, LED light strip, cool touch door, USB port, multi point food probe, drain water tempering, 156,000 BTU, 120v/60/1-ph cord with plug, cULus, NSF, (VPJ102G-81)

NOTE: Item qualifies for a no charge equipment check out after the unit has been fully installed & put into service. contact your Vulcan Representative for more details
1 year limited parts & labor warranty, standard
K-12 School Nutrition extended warranty extends the warranty for 12 months beyond the 12 month Original Equipment Warranty, not to exceed 24 months from date of installation
Filtration System

NOTE: Water is a customer supplied utility just like Gas & Electric to the equipment. Proper Water Filtration based on customer water quality is essential to meet the equipment water spec requirements. Verify type of filtration needed based on performing a cold water analysis from the customer site. A suitable Water Treatment System & regular filter replacements coupled with routine cleaning/deliming is required.
V3MRO-2 Reverse Osmosis Water Filtration System, up to 200 gpd capacity (double combi units), minimum 60 psi/maximum 125psi, minimum 40°/maximum 100°, Common treatment for sediment, chloramines, chlorine, chloride, hardness & TDS reduction, integrated pump & storage tank, includes: wall-mount bracket, quick disconnect plumbing & special installation fittings kit for Vulcan Combi Oven/Steamers with standard 3/4" water lines & spray hose

TCM-RACK102 (5) Grab-and-Go Racks for, 18" x 26" pans on TCM units, standard
TCM-PROBE3 Multi-Point Food Probe, standard

VDL-1 Vulcan Detergent Liquid, 2.5 gal each, (2) per case (sold per case)
VRL-1 Vulcan Rinse Liquid, 2.5 gal each, (2) per case (sold per case)
(2) HOSEWTR 3/4BBV Flex stainless steel water hose 72", 3/4" female NSHT (2 per unit required for gas & electric, 3 with filter system, 1 per unit for direct steam)
TCM-STAND2 Deluxe Stand, with pan supports for 102 TCM units

INSTALLATION Delivery and Installation of new Combi Oven and Water Treatment System. Make Final Connections and check operation of equipment. To be Provided by:

Hobart Service
43442 N Interstate 94 Service Dr.
Belleville, MI 48111
P:734-697-3070

ITEM 2 -GAS CONNECTOR HOSE KIT / ASSEMBLY (1 kt REQ'D)

T&S Brass Model HG-2D-48SK

Safe-T-Link Gas Connector Kit, 3/4" connection, 48" hose, stainless steel braiding with extruded coating, (2) Swivelink fittings, (1) 90° elbow, ball valve, necessary hardware, with Surelink restraining cable adjustable for 3' to 5', 215,000 BTU/ hr minimum flow capacity

KRAUSE ELEMENTARY SCHOOL

ITEM 1-COMBI OVEN, GAS (1 REQ'D)

Vulcan Model TCM-102G-NAT/LP Dimensions: 42.08(h) x 36.22(w) x 33.3(d)

Touch Combi Multi (TCM), 10 level full size, gas, boilerless, (10) 18"x 26"x 1" full sheet pan or (20) 12"x 20"x 2.5" steam pan capacity, (5) Grab n Go wire racks, twin control touch & knob, LCD display, Exclusive ABC, with JET & AUTO controls interface, customizable recipes & factory pre-programmed, automatic cleaning with recirculation, auto descale, non proprietary chemicals, auto-reversing fan, LED light strip, cool touch door, USB port, multi point food probe, drain water tempering, 156,000 BTU, 120v/60/1-ph cord with plug, cULus, NSF, (VPJ102G-81)

NOTE: Item qualifies for a no charge equipment check out after the unit has been fully installed & put into service. contact your Vulcan Representative for more details
1 year limited parts & labor warranty, standard

K-12 School Nutrition extended warranty extends the warranty for 12 months beyond the 12 month Original Equipment Warranty, not to exceed 24 months from date of installation
Filtration System

NOTE: Water is a customer supplied utility just like Gas & Electric to the equipment. Proper Water Filtration based on customer water quality is essential to meet the equipment water spec requirements. Verify type of filtration needed based on performing a cold water analysis from the customer site. A suitable Water Treatment System & regular filter replacements coupled with routine cleaning/deliming is required.

V3MRO-2 Reverse Osmosis Water Filtration System, up to 200 gpd capacity (double combi units), minimum 60 psi/maximum 125psi, minimum 40°/maximum 100°, Common treatment for sediment, chloramines, chlorine, chloride, hardness & TDS reduction, integrated pump & storage tank, includes: wall-mount bracket, quick disconnect plumbing & special installation fittings kit for Vulcan Combi Oven/Steamers with standard 3/4" water lines & spray hose

TCM-RACK102 (5) Grab-and-Go Racks for, 18" x 26" pans on TCM units, standard

TCM-PROBE3 Multi-Point Food Probe, standard
VDL-1 Vulcan Detergent Liquid, 2.5 gal each, (2) per case (sold per case)
VRL-1 Vulcan Rinse Liquid, 2.5 gal each, (2) per case (sold per case)
(2) HOSEWTR 3/4BBV Flex stainless steel water hose 72", 3/4" female NSHT (2 per unit
required for gas & electric, 3 with filter system, 1 per unit for direct steam)
TCM-STAND2 Deluxe Stand, with pan supports for 102 TCM units

INSTALLATION Delivery and Installation of new Combi Oven and Water Treatment
System. Make Final Connections and check operation of equipment. To be Provided by:

Hobart Service
43442 N Interstate 94 Service Dr.
Belleville, MI 48111
P:734-697-3070

ITEM 2 -GAS CONNECTOR HOSE KIT / ASSEMBLY (1 kt REQ'D)

T&S Brass Model HG-2D-48SK

Safe-T-Link Gas Connector Kit, 3/4" connection, 48" hose, stainless steel braiding with extruded coating,
(2) Swivelink fittings, (1) 90° elbow, ball valve, necessary hardware, with Surelink restraining cable
adjustable for 3' to 5', 215,000 BTU/ hr minimum flow capacity